

**Mobil 1**

Mobil Lubricants Workshop Guide (UK)

With effect from 1st July 2010

For more information on our products and services please visit us at www.mobil1.co.uk or www.mobil.co.uk

Description	Bulk	208 litre barrel	20 litre pail	5 litre pack (4 per case)	1 litre pack (12 per case)	Product Applications
ENGINE OILS						
Mobil 1 ESP Formula 5W-30	(146227)	(146228)	(146230)	(151055)	(151054)	Fully synthetic, low ash product with wide application, including DPF. Meets the requirements of: ACEA:C2/C3, API: CF, JASO DL-1. Approved: BMW LL-04, VW 504 00 / 507 00, Peugeot/Citroen: PSA B71 2290, MB-Approval 229.31 / MB-Approval 229.51, Porsche C30.
Mobil 1 New Life 0W-40	(150050)	(150027)	(150029)	(151048)	(151047)	Fully synthetic product covering a wide range of applications. Meets the requirements of: ACEA: A3/B3 A3/B4, API: SM/CF. Approved: BMW LL-01, VW502 00/ 505 00, MB-Approval 229.3 / MB-Approval 229.5, Porsche A40.
Mobil 1 Turbo Diesel Formula 0W-40				(151041)	(151040)	Fully synthetic product covering a wide range of diesel applications. Meets the requirements of: ACEA: A3/B3 A3/B4, API: CF. Approved: BMW LL-01, VW502 00/ 505 00, MB-Approval 229.3 / MB-Approval 229.5.
Mobil 1 Fuel Economy 0W-30	(143501)	(143502)	(143504)		(151063)	Fully synthetic, fuel economy product. Meets the requirements of: ACEA: A1/B1, A5/B5, API: SL/CF.
Mobil 1 0W-20		(150690)			(150957)	Fully synthetic product. Meets the requirements of: ACEA: A1/B1, API: SM/CF. ExxonMobil recommends this product for Toyota Optimal Drive, petrol engines.
Mobil 1 Extended Life 10W-60		(150040)		(151069)	(151068)	Fully synthetic product for motorsport applications. Meets the requirements of: ACEA: A3/B3, A3/B4, API: SM/CF.
Mobil Super 3000 Formula C1 5W-30	(151298)	(151311)				Fully synthetic Low Ash product. Meets the requirements of ACEA: C1. Meets Ford specification: WSS-M2C934-B.
Mobil Super 3000 Formula R 5W-30		(150689)			(150886)	Fully synthetic product. Meets the requirements of: ACEA: C4. Approved: Renault RN0720.
Mobil Super 3000 Formula P 5W-30	(151193)	(151194)			(151310)	Fully synthetic low ash product. Meets the requirements of: ACEA: C2, API: CF. Approved: Peugeot/Citroen PSA B71 2290. ExxonMobil recommends this product for all Toyota diesel engines from 2006 onwards.
Mobil Super 3000 X1 5W-40	(150008)	(150010)	(150011)	(151166)	(151165)	Fully synthetic premium product. Meets the requirements of: ACEA: A3/B3, A3/B4, API: SM/CF. Approved: BMW LL-01, VW502 00/505 00, Peugeot/Citroen: PSA B71 2296, MB-Approval 229.3, Renault RN0710.
Mobil Super 3000 Formula G 5W-30	(151233)	(151236)				Fully synthetic product. ExxonMobil recommends this product as suitable for use in applications requiring GM dexos2.
Mobil Super FE Special 5W-30	(104457)	(125902)		(150824)	(142437)	Fully synthetic product for Ford and Mazda petrol application. Meets Ford specifications: WSS-M2C913-A / WSS-M2C913-B. Meets the requirements of: ACEA: A1/B1. API: SL.
Mobil Super 2000 Formula P 10W-40	(151093)	(151094)			(151096)	Semi-synthetic product for PSA and Renault. Meets the requirements of: ACEA: A3/B3, A3/B4, API: SL/CF. Approved: Peugeot/Citroen: PSA B71 2294, Renault RN0700.
Mobil Super 2000 X1 10W-40	(150014)	(150015)	(150016)	(151187)	(151188)	Semi-synthetic general application product. Meets the requirements of: ACEA: A3/B3, API: SL/CF. Approved: VW501 01 / 505 00, MB-Approval 229.1.
Mobil Super 2000 X1 Diesel 10W-40				(151183)	(151184)	Semi-synthetic general application diesel product. Meets the requirements of: ACEA: A3/B3, API: CF. Approved: VW501 01 / 505 00, MB-Approval 229.1.
COMMERCIAL OILS						
Mobil Delvac XHP LE 10W-40	(146488)	(146489)		(149620)*		Synthetic, low ash, long drain product for commercial application. Meets the requirements of ACEA E6/E4/E7, API CH4. Approvals include MB-Approval 228.51, MAN M 3477, Volvo VDS-3.
Mobil Delvac XHP Extra 10W-40	(104416)	(121732)	(121737)	(148369)*		Synthetic, long drain product for commercial application. Meets the requirements of ACEA E4/E7. Approvals include: MB-Approval 228.5, MAN M 3277, Volvo VDS-3, Scania LDF-2.
Mobil Delvac MX 15W-40	(104420)	(121641)	(121650)	(148370)*		Mixed fleet product. Meets the requirements of: ACEA E7, B4, B3 and API CH4/SL. Approvals include MB-Approval 228.3, MAN M 3275, Volvo VDS-3.

Description	Bulk	208 litre barrel	20 litre pail	5 litre pack (4 per case)	1 litre pack (12 per case)	500ml pack (6 per case)	Product Applications
TRANSMISSION OILS							
Mobilube 1 SHC 75W-90		(104480)	(123716)		(142382)		Fully Synthetic gear and axle oil API GL-4 and 5
Mobilube SHC-V		(150355)	(150356)				Fully Synthetic gear lubricant (Voith Turbo approved)
Mobilube LS 85W-90		(123805)	(127838)				Mineral axle oil with Limited Slip capability
Mobilube XHP 75W-80		(123850)	(123852)				Semi Synthetic transmission oil to API GL-4. Excels at synchromesh performance.
Mobilube HD 80W-90		(123570)	(127732)		(142390)		Mineral axle oil but sometimes recommended for gearboxes, API GL-5.
Mobilube HD-A 85W-90	(143910)	(143912)	(143914)		(142388)		Mineral axle oil aimed at Mercedes Benz applications
BV 75W-80			(111482)		(144415)		Manual gearbox oil for use in majority of Peugeot models
Mobilube GX-A 80W	(143941)	(143943)	(143870)				Mineral gearbox oil aimed at Mercedes Benz applications
Mobilube GX 80W-90	(123763)	(123771)	(141064)		(142385)		Mainstream Mineral gearbox oil
Mobil ATF LT 71141	(151006)	(151007)	(151008)		(151010)		Automatic transmission oil specific application for BMW and Jaguar
Mobil ATF SHC		(121201)	(127579)		(142369)		Automatic transmission oil to quality level Dexron IIE.
Mobil ATF 320	(146406)	(146408)	(146409)		(146412)		Automatic transmission oil to quality level Dexron IIIG.
Mobil ATF 134		(150687)	(150688)				Extra high performance automatic transmission oil, for Mercedes Benz 7-speed automatic transmission gearboxes. It is approved against MB-Approval 236.14.
Mobil ATF 200		(121132)	(143096)				Automatic transmission fluid, quality level: TASA. MB-Approval 236.2.
Mobil ATF 220	(104427)	(121169)	(127577)	(142216)*	(142456)		Automatic transmission oil to quality level Dexron IID.
Mobil Gear Oil VS 600			(122906)				Fully synthetic 75W-90 API GL-5 gear oil. Suitable for BMW non limited slip differentials.
Mobil Gear Oil VS 500			(122902)				Fully synthetic 75W-140 API GL-5 gear oil. Suitable for BMW limited slip differentials.
ANCILLARIES							
Mobil Antifreeze Advanced		(144271)	(144272)	(144195)	(144194)		
Mobil Antifreeze Extra		(144275)	(144276)				
Mobil Antifreeze		(144279)	(144150)	(144199)			
Mobil Brake Fluid Dot 4		(144157)				(144335)**	
GREASE (Price per kilogram)							
	180kg drum	50kg keg	18kg keg	0.4kg cartridge (12 per case)			
Mobilgrease XHP222 (Blue Grease)	(123275)	(123277)	(146379)	(149410)			

* 4 litre pack (4 per case)

** 12 per case

TERMS AND CONDITIONS OF SALE

Orders for products will be accepted subject to ExxonMobil Petroleum & Chemical bvba standard terms and conditions applying at the time. Customers will be supplied with a copy of such terms and conditions upon request and will be deemed to have notice of the same prior to placing an order.

Packed lubricant products can only be returned after due consultation if related to your most recent order. Packed products returns which do not meet the criteria will in principle NOT be credited. Please check your deliveries on receipt or notify us promptly (maximum of 5 working days).

Accounts are payable on, or before, the 20th day of the month following invoice date.

THE MINIMUM ORDER OF ANY PACKED PRODUCT IN FULL CASES IS 100 LITRES TO ONE ADDRESS

THE MINIMUM DELIVERY OF ANY ONE GRADE IN BULK HOSE IS 1000 LITRES



Electronic Order Management

Visit: <http://portal.exxonmobil.com>

or telephone **0800 0857420** for further details